

REVISED STARTING
SERIAL # 220610593



PARTS LIST MANUAL HSS-14G & HSS-14E



GASOLINE MODEL



ELECTRIC MODEL

14" HARDSCAPE SAWS

SKU #	MODEL #	POWER OPTION
24800	HSS-14G	HONDA GASOLINE ENGINE MODEL GX160
26200	HSS-14E	BALDOR ELECTRIC MOTOR 1.5HP-1PH-60Hz-115V/20A

**READ AND UNDERSTAND THE OPERATOR'S SAFETY MANUAL THOROUGHLY
BEFORE ATTEMPTING TO OPERATE THIS EQUIPMENT.**

Death or serious injury could occur if this machine is used improperly.

Machine specific Operator's Instruction Manuals are offered at edcoinc.com/customer-support/parts-and-manuals
READ AND UNDERSTAND THE ENGINE MANUFACTURERS INSTRUCTIONS AND OPERATORS MANUAL BEFORE OPERATION.



EQUIPMENT DEVELOPMENT COMPANY, INC.

100 Thomas Johnson Drive, Frederick, MD 21702-4600 USA
Phone: 800-638-3326 or 301-663-1600 • Fax: 800-447-3326 or 301-663-1607
Website: www.edcoinc.com • E-mail: techsupport@edcoinc.com

Printed in USA
JWA ©2022



SAFETY INFORMATION



SAFETY MESSAGES

• Safety Instructions are preceded by a graphic alert symbol of DANGER, WARNING, or CAUTION.



Indicates an imminent hazard which, if not avoided, will result in death or serious injury.



Indicates an imminent hazard which, if not avoided, can result in death or serious injury.



Indicates hazards which, if not avoided, could result in serious injury and or damage to the equipment.

GASOLINE / PROPANE POWERED EQUIPMENT



• Engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.



• Tilting a gasoline powered machine fitted with an EPA approved vented charcoal filter gas cap, beyond 20° can cause fuel leakage. If a leak occurs, do not

start or run the engine until the leak is fixed. Eliminate all other ignition sources in the immediate area (no smoking, flares, sparks or flames). Use approved gasoline absorbing material to contain the fuel leakage. Then use clean, non-sparking tools to collect absorbed materials then dispose of these contaminants properly.



• Gasoline is extremely flammable and poisonous. It should only be dispensed in well ventilated areas, and with a cool engine.

• Small gasoline engines produce high concentrations of carbon monoxide (CO) example: a 5 HP 4 cycle engine operation in an enclosed 100,000 cu. ft. area with only one change of air per hour is capable of providing deadly concentrations of CO in less than fifteen minutes. Five changes of air in the same area will produce noxious fumes in less than 30 minutes. Gasoline powered equipment should not be used in enclosed or partially enclosed areas. Symptoms of CO poisoning include, head-ache, nausea, weakness, dizziness, visual problems and loss of consciousness. If symptoms occur - get into fresh air and seek medical attention immediately.

- Never refuel a hot engine or an engine while it is running.
- Engines are shipped from factory without fuel/oil.



• Propane is extremely flammable and is heavier than air and tends to settle in low areas where a spark or flame could ignite gas. DO NOT start or operate this propane engine in a poorly ventilated area where leaking propane gas could accumulate and endanger safety of persons in area. If headache develops, shut off machine. Have it checked for carbon monoxide emissions by a qualified technician before using it again. To ensure personal safety, installation and repair of propane fuel supply systems must be performed only by qualified technicians. Carbon monoxide emissions from this machine are greatly increased due to a dirty combustion air cleaner.

ELECTRICAL POWERED EQUIPMENT



Extreme care must be taken when operating electric models with water present: Ensure power cord is properly grounded, is attached to a Ground-Fault-Interrupter (GFI) outlet, and is undamaged.

- Check all electrical cables - be sure connections are tight and cable is continuous and in good condition. Be sure cable is correctly rated for both the operating current and voltage of this equipment.
- Improper connection of the equipment grounding conductor can result in a risk of electric shock. Check with qualified electrician or service person if there is any doubt as to whether the outlet is properly grounded. Adhere to all local codes and ordinances.
- NOTE: In the event of a malfunction or breakdown, grounding provides a path of least resistance for the electric current to dissipate. The motor is equipped with a grounded plug and must be connected to an outlet that is properly installed and properly grounded. DO NOT modify the plug provided on the motor. If the plug does not fit the outlet have a qualified electrician install the proper receptacle.

ELECTRICAL POWERED EQUIPMENT CONTINUED

- Do not disconnect power by pulling cord. To disconnect, grasp the plug, not the cord.
- Unplug power cord at the machine when not in use and before servicing.
- Switch motor OFF before disconnecting power.
- Never use frayed, damaged, taped or under rated extension cords. Electrical shock could result in death or serious injury to the operator and damage to the equipment.
- Assure you are using the proper extension cord length.

GENERAL INSTRUCTIONS

- Equipment should only be operated by trained personnel in good physical condition and mental health (not fatigued). The operator and maintenance personnel must be physically able to handle the bulk weight and power of this equipment.
- This is a one person tool. Maintain a safe operating distance to other personnel. It is the operators' responsibility to keep other people (workers, pedestrians, bystanders, etc.) away during operation. Block off the work area in all directions with roping, safety netting, etc. Failure to do so may result in others being injured by flying debris or exposing them to harmful dust and noise.

- This equipment is intended for commercial use only.
- For the operator's safety and the safety of others, always keep all guards in place during operation.
- Never let equipment run unattended.



- Personal Protection Equipment and proper safety attire must be worn when operating this machinery. The operator must wear approved safety equipment appropriate for the job such as hard hat and safety shoes when conditions require. Hearing protection **MUST** be used when operational noise levels of this equipment may exceed 85db. Eye protection **MUST** be worn at all times.



Keep body parts, loose clothing and accessories away from moving parts. Failure to do so could result in dismemberment or death.



- Do not modify the machine.
- Stop motor/engine when adjusting or servicing this equipment. Maintain a safe operating distance from flammable materials. Sparks from the cutting-action of this machine can ignite flammable materials or vapors.

DUST WARNING



Some dust created by power sanding, sawing, grinding, drilling, and other construction activities contains chemicals known to cause cancer, birth defects, or other reproductive harm. Materials being removed can be toxic or hazardous. A breathing respirator is required to help protect the operator. Some examples of these chemicals are:

- Lead from lead-based paints.
- Crystalline silica from bricks, concrete and other masonry products. Your risk of exposure to these chemicals varies depending on how often you do this type of work. To reduce your risk: work in a well ventilated area, use a dust control system, such as an industrial-style vacuum, and wear approved personal safety equipment, such as a dust/particle respirator designed to filter out microscopic particles.
- See more on the importance of dust prevention and silica warnings at: osha.gov/silica
- More concrete and silica dust suppression training and educational materials available at edcoinc.com/silica-standards or scan the QR code on page 5.
- Written exposure plans are provided at <http://www.edcoinc.com/written-exposure-control-plans/>

PARTS LIST MANUAL

HSS-14G & HSS-14E 14" HARDSCAPE SAW

TABLE OF CONTENTS

<u>Section</u>	<u>Page Number</u>
Safety Information	2
How To Order Replacement Parts	3
Illustration 1: Main Grouping	4, 5
Illustration 2: Pan & Roll Table Grouping	6, 7
Illustration 3: Arbor Assembly	8
Illustration 4: Rolling Table Assembly	9
Illustration 5: Engine Grouping	10
Illustration 6: Motor Grouping	11
Wiring Diagram for Baldor 60Hz Motor	12
Decal Sheet: P/N 92210.	13
Notes	14
Limited Equipment Warranty of Sale	15
STOP - Before Using This Product	16

HOW TO ORDER REPLACEMENT PARTS

- ☐ To insure product safety and reliability, always use genuine EDCO replacement parts when making repairs to the equipment.
- ☐ When calling for parts, specify the MODEL and SERIAL number of the machine, which can be found on the NAME PLATE. Keep that information in the space provided. In addition to this information, give part number, description, and quantity as listed on the parts list to your parts representative.
- ☐ Please note: Due to improvements and changes in the equipment, the illustrations shown may be different than the actual machine.


FILL IN INFORMATION BELOW

Date of Purchase _____


Model # _____

Serial # _____

SKU # _____


ILLUSTRATION 1: MAIN GROUPING

PARTS LISTING - ILLUSTRATION 1: MAIN GROUPING			
ITEM #	PART #	DESCRIPTION	QTY.
1	42301	MAIN FRAME, HSS-14	1
2	42148	PLUG, SQ. TUBE 1-1/2 X 11 GA., BLK	2
3	42302	DECK, ENGINE & ARBOR, HSS-14	1
4	10021	SCREW, CAP 3/8-24 X 1 ZINC	4
5	11695	WASHER, 1.100 X .406 X .120	4
6	10312	WASHER, FLAT 1/2 SAE ZINC *USE AS REQ'D. TO LEVEL DECK	*
7	10004	NUT, HEX LOCK 3/8-24 ZINC	4
8	40056A	ARBOR ASSY. W/ 2.75" 2GR.3V SHEAVE (GAS)	1
	40056C	ARBOR ASSY. W/ 2.25" 2GR.3V SHEAVE (ELEC.) NOTE: REFER TO ILLUS. 3 FOR BREAKDOWN.	1
9	10048	SCREW, CAP 5/16-24 X 3/4	4
10	10801	WASHER, LOCK 5/16 ZINC	4
11	10213	WASHER, FLAT 5/16 SAE ZINC	4
12	40012	FLAP, SPLASH 2-1/2 X 7	1
13	11811	BOLT, FLANGE 1/4-20 X 3/4 ZINC	4
14	10602	WASHER, FLAT 1/4 SAE ZINC	2
15	10861	NUT, KEPS LOCK 1/4-20 ZINC	2
16	42305	GUARD, BLADE 14", HSS-14	1
17	99323	BARBED FITTING, "Y" 1/4"HOSE	1
18	42314	HOSE 1/4"ID X 6-1/4"L, HSS-14	2
19	42313	HOSE 1/4"ID X 24"L, HSS-14	1
20	10762	CLAMP, HOSE, SPRING-BAND 3/8" GREEN	1
21	42312	BARB, 5/16HOSE X 1/4MPT	1
22	10711A	VALVE & HOSE CONNECTOR ASSY.	1
23	10053	SCREW, CAP 5/16-18 X 3/4	2
24	10807	NUT, HEX LOCK 5/16-18 ZINC	2
25	80011	KNOB, 3-PRONG W/ 3/8-16 THD.	2
26	10025	WASHER, FLAT 3/8 SAE ZINC	4
27	42306	COVER, BELT, HSS-14	1

ILLUSTRATION 2: PAN & ROLL TABLE GROUPING


PARTS LISTING - ILLUSTRATION 2: PAN & ROLL TABLE GROUPING			
ITEM #	PART #	DESCRIPTION	QTY.
1	42301	MAIN FRAME, HSS-14 (SEE ILLUS. 1, ITEM 1)	1
2	42303	PAN, HSS-14	1
3	42304	TRACK RAIL 36-3/4"L, HSS-14	2
4	10018	SCREW, CAP 1/4-20 X 3/4	4
5	10602	WASHER, FLAT 1/4 SAE ZINC	4
6	10861	NUT, KEPS LOCK 1/4-20 ZINC	4
7	40378	STOPPER ASSEMBLY 1-1/2"	1
8	57148	GROMMET 3/8ID X 1/8GRV. X 5/8GD	4
9	42309	WASHER, FENDER 1/4 X 1"OD (S.S.)	4
10	42308	SCREW, SDHW 1/4 X 1 S.S.	4
11	42229	MOUNTING BRKT., VACUUM PORT TUBE	1
12	10834	SCREW, CAP 1/4-20 X 1/2 ZINC	2
13	10861	NUT, KEPS LOCK 1/4-20 ZINC	2
14	42307	VACUUM PORT TUBE, HSS-14	1
15	51078	PLUG, SQ. TUBE 1 X 14 GA., BLACK	1
16	42315	TABLE COMPLETE, ROLLING, HSS-14 (REFER TO ILLUS. 4 FOR BREAKDOWN)	1

ILLUSTRATION 3: ARBOR ASSEMBLY




ITEM #	PART #	DESCRIPTION	QTY.
1	40056A	ARBOR ASSY. W/ 2.75" 2GR.3V SHEAVE (GAS)	1
	40056C	ARBOR ASSY. W/ 2.25" 2GR.3V SHEAVE (ELEC.)	1
2	10321	SCREW, CAP 1/2-20 X 1-1/4	1
3	40023	ARBOR BLADE CAP 4", MASONRY SAW	1
4	40022	ARBOR BACKING PLATE 4", MASONRY SAW	1
5	40018	BEARING, RADIAL BALL 20X47X20.6MM	2
6	40036	KEY, WOODRUFF 1/8 X 3/8 (#403)	1
7	40021	ARBOR SHAFT 8-7/8"L GMS/MS/HSS-14	1
8	40020	ARBOR HOUSING, MS/GMS-14 & HSS-14	1
9	10170	KEY 3/16SQ X 1-3/4	1
10	40694	SHEAVE 2.75"OD X 2GR.3V X 3/4"BORE (GAS)	1
	40074	SHEAVE 2.25"OD X 2GR.3V X 3/4"BORE (ELEC.)	1

ILLUSTRATION 4: ROLLING TABLE ASSEMBLY




ITEM #	PART #	DESCRIPTION	QTY.
1	42315	TABLE COMPLETE, ROLLING (INCLUDES ITEMS 2 THRU 18)	1
2	42226	TABLE, ROLLING, GMS-10 & HSS-10/14	1
3	42222	RUBBER PAD 12 X 7-1/2 X 3/16	1
4	42221	RUBBER PAD 12 X 8 X 3/16	1
5	14082	PULLEY BEARING 1-1/4DIA. X 1/4BORE	4
6	10031	SCREW, CAP 1/4-20 X 1	5
7	10602	WASHER, FLAT 1/4 SAE ZINC	13
8	10861	NUT, KEPS LOCK 1/4-20 ZINC	8
9	42311	TABLE FRONT PANEL, HSS-14 (2 PCS.)	1
10	10018	SCREW, CAP 1/4-20 X 3/4	3
11	42106	LATCH, ROLLING TABLE	1
12	10015	NUT, HEX LOCK 1/4-20 ZINC	1
13	40689A	GUIDE ASSY., CUT, UNIVERSAL (INCLUDES ITEMS 17 THRU 21)	1
14	40425	KNOB, 3-PRONG W/ 3/8-16 X 5/8 STUD	1
15	42015	BLOCK, CUT GUIDE, MASONRY SAW	1
16	40689	BRACKET, CUT GUIDE, UNIVERSAL	1
17	10801	WASHER, LOCK 5/16 ZINC	1
18	10053	SCREW, CAP 5/16-18 X 3/4	1

ILLUSTRATION 5: ENGINE GROUPING



ITEM #	PART #	DESCRIPTION	QTY.
1	40387	ENGINE, HONDA GX160U1-QXC9 CYC.A.C.	1
2	40327	OIL DRAIN KIT, 4 THRU 6.5 HP HONDA	1
3	10918	BOLT, CARRIAGE 5/16-18 X 1-3/4 F.T.	4
4	10213	WASHER, FLAT 5/16 SAE ZINC	4
5	10801	WASHER, LOCK 5/16 ZINC	4
6	10054	NUT, HEX 5/16-18 ZINC	4
7	10410	BOLT, TAP 3/8-16 X 2-1/2 (FULL THD)	1
8	10404	NUT, HEX 3/8-16 ZINC	1
9	N/A	KEY 3/16"SQ (INCLUDED W/ ENGINE)	1
10	40694	SHEAVE 2.75"OD X 2GR.3V X 3/4"BORE	1
11	10276	BELT 3VX-355	2

ILLUSTRATION 6: MOTOR GROUPING




ITEM #	PART #	DESCRIPTION	QTY.
1	16092	MOTOR, BALDOR 1.5HP-1P 60HZ 1725RPM	1
	16563	REPLACEMENT PARTS: CAPACITOR, START, BALDOR EC1270A02, 270-324 MFD, 125V	1
	16164	CAPACITOR, RUN, BALDOR OC3040F18SP, 40MFD 370V	1
	16564	RESET BUTTON, BALDOR TPCRT50CB	1
	16510	SWITCH, TOGGLE DPST 20A SPAD	1
2	40041	CONNECTOR, LOCKING 20A/125V L5-20C	1
3	42237	MOUNT BRKT., MOTOR, GMS10 HSS14	1
4	10818	BOLT, CARRIAGE 5/16-18 X 3/4	6
5	10819	BOLT, CARRIAGE 5/16-18 X 1	2
6	10213	WASHER, FLAT 5/16 SAE ZINC	4
7	10801	WASHER, LOCK 5/16 ZINC	8
8	10054	NUT, HEX 5/16-18 ZINC	8
9	10060	KEY 3/16SQ X 1-1/4	1
10	40073	SHEAVE 3.15"OD X 2GR.3V X 3/4"BORE	1
11	10276	BELT 3VX-355	2

MODEL HSS-14E

WIRING DIAGRAM FOR BALDOR 60Hz MOTOR

BALDOR SPEC. 35V801L853G1



DECAL SHEET: P/N 92210

P/N 92210 Rev.D

HSS-14, GMS-10 & TMS-10

14x17 Sheet



WARNING: Cancer and Reproductive Harm.
For more information, go to www.P65Warnings.ca.gov



**THIS OUTLET
FOR WATER
PUMP ONLY!**
Unplug the Water Pump
when cutting dry

115 VOLTS

230 VOLTS


SINGLE PHASE



CAUTION
GENERATOR SIZE REQUIREMENT
RATE GENERATOR AT 3 TIMES
MOTOR RATED HORSEPOWER



THROTTLE



RESET


CHECK OIL DAILY

exceeds 85dBA

WARNING

THERE IS NO OIL IN THIS MACHINE

RENTAL-TOUGH®



NOTES

Record here any repairs or changes made to the Equipment

LIMITED EQUIPMENT WARRANTY OF SALE

Equipment Development Company, Inc. herein referred to as EDCO (Seller) warrants that each new unit manufactured by EDCO to be free from defects in material and workmanship in normal use and service for a period of (1) one year (except for the cutter drum assembly on all model concrete/asphalt planers AND the chisel head assembly on all model ALR's & ALR-BS in which case the warranty period shall be 90 days) from date of shipment to the original retail or equipment rental center owner.

Accessories or equipment furnished and installed on the product by EDCO but manufactured by others, including, but not limited to engines, motors, electrical components, transmissions etc., shall carry the accessory manufacturers own warranty.

EDCO will, at its option, repair or replace, at the EDCO factory or at a point designated by EDCO, any part which shall appear to the satisfaction of EDCO inspection to have been defective in material or workmanship.

EDCO reserves the right to modify, alter and improve any part or parts without incurring any obligation to replace any part or parts previously sold without such modified, altered or improved part or parts.

This warranty is in lieu of and excludes all other warranties, expressed, implied, statutory, or otherwise created under applicable law including, but not limited to the warranty of merchantability and the warranty of fitness for a particular purpose in no event shall seller or the manufacturer of the product be liable for special, incidental, or consequential damages, including loss of profits, whether or not caused by or resulting from the negligence of seller and/or the manufacturer of the product unless specifically provided herein. In addition, this warranty shall not apply to any products or portions thereof which have been subjected to abuse, misuse, improper installation, maintenance, or operation, electrical failure or abnormal conditions and to products which have been tampered with, altered, modified, repaired, reworked by anyone not approved by seller or used in any manner inconsistent with the provisions of the above or any instructions or specifications provided with or for the product.

TERMS AND CONDITIONS

(NOT APPLICABLE TO SALES THROUGH AUTHORIZED DISTRIBUTION)

FORCE MAJEURE

Seller's obligation hereunder are subject to, and Seller shall not be held responsible for, any delay or failure to make delivery of all or any part of the Product due to labor difficulties, fires, casualties, accidents, acts of the elements, acts of God, transportation difficulties, delays by a common carrier, inability to obtain Product, materials or components or qualified labor sufficient to timely perform part of or all of the obligations contained in these terms and conditions, governmental regulations or actions, strikes, damage to or destruction in whole or part of manufacturing plant, riots, terrorist attacks or incidents, civil commotions, warlike conditions, flood, tidal waves, typhoon, hurricane, earthquake, lightning, explosion or any other causes, contingencies or circumstances within or without the United States not subject to the Seller's control which prevent or hinder the manufacture or delivery of the Products or make the fulfillment of these terms and conditions impracticable. In the event of the occurrence of any of the foregoing, at the option of Seller, Seller shall be excused from the performance under these Terms and Conditions, or the performance of the Seller shall be correspondingly extended.

This document sets forth the terms and conditions pursuant to which the purchaser ("Purchaser") will purchase and Equipment Development Co. Inc. ("Seller") will sell the products, accessories, attachments (collectively the Products) ordered by the Purchaser. These terms and conditions shall govern and apply to the sale of Seller's Products to Purchaser, regardless of any terms and conditions appearing on any purchase order or other forms submitted by Purchaser to Seller, or the inconsistency of any terms therein and herein.

1. PRICE

All prices set forth on any purchase order or other document are F.O.B. Sellers facility or distribution point, as may be determined by Seller (F.O.B. Point). All prices are exclusive of any and all taxes, including, but not limited to, excise, sales, use, property or transportation taxes related to the sale or use of the Products, now or hereafter imposed, together with all penalties and expenses. Purchaser shall be responsible for collecting and/or paying any and all such taxes, whether or not they are stated in any invoice for the Products. Unless otherwise specified herein, all prices are exclusive of inland transportation, freight, insurance and other costs and expenses relating to the shipment of the Products from the F.O.B. point to Purchaser's facility. Any prepayment by Seller of freight insurance and other costs shall be for the account of Purchaser and shall be repaid to Seller.

2. PAYMENT TERMS

Payment terms are as follows. 2% 10 days (to approved and qualified accounts). Net 30 days. This is a cash discount for invoices paid within 10 days after the invoice date, regardless of date of receipt of shipment. This is not a trade discount and will not be granted to accounts that do not adhere to stated terms.

*All past due accounts are subject to a late payment fee of 1.5% per month or a maximum allowed by law if different, along with the expenses incidental to collection including reasonable attorney's fees and costs.

*Seller reserves the right to hold shipments against past due accounts.

*Seller reserves the right to alter payment terms.

3. FREIGHT TERMS

All shipments will be made F.O.B. shipping point as designated in these Terms and Conditions, and title shall pass at the F.O.B. point. Delivery to the initial common carrier shall constitute delivery to the Purchaser. Any claims for loss or damage during shipment are to be filed with carrier by the Purchaser. Seller will not assume responsibility for the performance of the carrier.

Back orders will be shipped in the most practical fashion with charges consistent with our freight policy established with the original order. UPS, FED EX, MAIL or shipments by other couriers are subject to the same terms and conditions as outlined in paragraph #3 "Freight Terms".

4. DELIVERY, DAMAGES, SHORTAGES

Seller shall use reasonable efforts to attempt to cause the Products to be delivered as provided for in these Terms & Conditions. Delivery to the initial common carrier shall constitute the delivery to the Purchaser. Seller's responsibility, in so far as transportation risks are concerned ceases upon the delivery of the Products in good condition to such carrier at the F.O.B. point and all the Products shall be shipped at the Purchaser's risk. Seller shall not be responsible or liable for any loss of income and/or profits, or incidental, special, consequential damages resulting from Seller's delayed performance in shipment and delivery.

5. RETURN OF DEFECTIVE PRODUCTS

Defective or failed material shall be held at the Purchaser's premises until authorization has been granted by Seller to return or dispose of Products. Products that are to be returned for final inspection must be returned Freight Prepaid in the most economical way. Credit will be issued for material found to be defective upon Seller's inspection based on prices at time of purchase.

6. PRODUCTS ORDERED IN ERROR

Products may be returned, provided that claim is made and Seller is notified within 7 days of receipt of Products, and the Products are in original buyer's possession not more than 30 days prior to return, subject to Seller's approval. If Products are accepted for return, they must be Freight Prepaid and buyer will be charged a minimum of 15% restocking charge, plus a charge back for outbound freight charges if the original order was shipped prepaid. Returns are not accepted for any Products that are specifically manufactured to meet the buyer's requirement of either specifications or quantity.

AGREEMENTS

These Terms and Conditions constitute the entire agreement between Seller and Purchaser as it relates to terms and conditions of sale, and supersedes any and all prior oral or written agreements, correspondence, quotations or understandings heretofore in force between the parties relating to the subject matter hereof. There are no agreements between Seller and Purchaser with respect to the Product herein except those specifically set forth in and made part of these terms and conditions. Any additional terms, conditions and/or prices are rejected by Seller.

These terms and conditions may be modified, cancelled or rescinded only by a written agreement of both parties executed by their duly authorized agents.

USE ONLY GENUINE EDCO PARTS & ACCESSORIES

For your own safety, the safety of others and the life of your machine.


SUBMIT ALL WARRANTY CLAIMS AT:

edcoinc.com/customer-support/warranty-claim-request/



BEFORE USING THIS PRODUCT

Have You Used EDCO's Online Customer Support??



Scan This QRC or Visit
www.edcoinc.com/customer-support



READ: **EDCO Owner's Manuals and Parts Listings** share basic information and parts of each product. Download and print them whenever needed.



WATCH: **EDCO Product Training Videos** show how to use products, install tooling, and perform basic maintenance.



Example Only

FIND: Somewhere on this product is an **EDCO QRC Training Decal**. Scanning this code provides owner's information, videos, and other training content anywhere/anytime on your mobile device.



JOIN: **EDCOed.com** is a free, 24-hour training space. Each certification track focuses on a specific EDCO product group. The information in these tracks help businesses be successful with those products.

EDCO is always updating online training / information so you always have the most recent content.

Also see Operator's Safety & Limited Warranty Manual

Equipment Development Co., Inc. • 800.638.3326 • techsupport@edcoinc.com