

## FLOOR GRINDERS SURFACE PREPARATION, FLOOR GRINDING & REMOVAL

SEC-NG	MODEL#	SEC-NG
	PART #	59800
SINGLE DISC FLOOR	POWER	Electric
	ENGINE/MOTOR	1.5HP, 115V/15A
GRINDER	PHASE	Single
	AMPS	13
	*RPMS	575
	LENGTH	43"
	WIDTH	21.75"
STRIP	HEIGHT	37.5"
GRIND REMOVE	WEIGHT	191 lbs
	ADDITIONAL MAX CORD LENGTH	25ft, 10 Gauge

PRODUCTION RATE: 10" working width grinds approximately 200-250 sq.ft. per hour at 1/32" depth per pass with diamond tooling.

**INCLUDES:** Multi-Tooling Disc, which accepts MAGNA-TRAP® tools, multi Vacuum Port and Water Port, 25 ft. 12 Gauge Power Cord attached with cord Hanger, 30lb weight pack

**REQUIRES:** 3 - Grinding Tools required per loading (directional Left-handed tooling)

## **IDEAL FOR:**

- Areas less than 1,500 square feet
- Residential & commercial applications
- **Grinding Concrete**
- Repairing damaged concrete slabs
- Removing urethanes or epoxy thin-
- Leveling high spots or surface imperfections
- Smoothing rough surfaces, rain marks or trowel marks
- Stripping mastics, thin-sets, paint buildups, resins and more





<sup>\*</sup> RPMs are based on the machine's accessory speed. \* NETHORSEPOWER STATEMENT - \*As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE j1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables. \*\* Call for availability. WARNING: CALIFORNIA PROPOSITION 65: Please read page 53 for warnings.