

## SS-30

### 30" SELF PROPELLED CONCRETE AND ASPHALT SAWS

MAX  
CUTTING  
DEPTH  
12"



MODEL #	SS-30	SS-30E
PART #	31400-30	34300-30
POWER	Gasoline	Electric
ENGINE/ MOTOR	Kohler CH980	15 HP, 460V/30A
PHASE	N/A	Three
AMPS	N/A	18.9
*RPMs	1900	1755
LENGTH	60.25	60.25
WIDTH	32"	32"
HEIGHT	51"	519"
WEIGHT	995 lbs	1094 lbs
MAX CORD LENGTH	N/A	250 ft, 10 Gauge

**PRODUCT NOTES:** Stress proof, precision machined, Steel arbor shaft. Includes electric start, 12 volt battery and heavy duty 30 amp charging system. Locking depth control allows operator to easily return to same depth, cut after cut. Positive-traction, chain-drive rear axle prevents slippage and improves cutting speeds. Swing away, rear 6.4 gallon fuel tank. Water pump included.

**REQUIRES** 1 -3 0" Concrete or Asphalt Blade.

#### IDEAL FOR:

- Highway, road and bridge repair
- Utility installation
- Patch repairs in asphalt and concrete
- Trenching

**THIS SAW IS STANDARD WITH A 30" BLADE GUARD.**

*\*RPM's are based on the saws blade speed for 30" blade capacity.*



SS-30

\* RPM's are based on the machine's accessory speed. \* NET HORSEPOWER STATEMENT - \*As rated by the engine manufacturer. The power rating of the engine indicated in this document is the net power output tested on a production engine for the engine model and measured in accordance with SAE j1349 at 3600 rpm. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the opening speed of the engine in application, environmental conditions, maintenance, and other variables. \*\* Call for availability.

**WARNING: CALIFORNIA PROPOSITION 65:** Please read page 53 for warnings.

1-800-638-3326 • edcoinc.com • edcostore.com • edcoed.com