

MAGNA-TRAP CORE 4 TOOLING

STRIP:

Soft Glue & Adhesive, Foam Rubber Carpet Backing, Flaking Paint, Soft Mastic, Paint Buildup
(*Strip off soft-material that can be cut with a utility knife)

MAGNA-BLADES

(8 Stripping Sides Per Replaceable Tungserts)

IDEAL FOR:

Stripping soft/thick coatings without grinding or removing concrete surfaces. (Packs of 3)

Classification: Directional
Concrete Surface Profile: CSP 0



LEFT-HAND
(For use on Single & Dual-Disc Grinders)
Part # 12501LC



RIGHT-HAND
(For use on Dual-Disc Grinders ONLY)
Part # 12501RC



PRO TUNGSTEN III CARBIDE REPLACEMENT PACK
Part # 300101 (Pack of 6)
with numbered edges 1-8

REMOVE:

Industrial Strength Coatings, Waterproof Membrane, Hard Thin Coverings, Pool Decks, Epoxy & Polyurea


PCD W/BACKING SEGMENT

IDEAL FOR:

Removing thick industrial coatings. This tool creates textured

concrete surfaces. (Packs of 3)

Classification: Directional
Concrete Surface Profile: CSP
Varies depending on application



LEFT-HAND
(Blue, For use on Single & Dual-Disc Grinders)
Part # QC-PCD1-LB



RIGHT-HAND
(Black, For use on Dual-Disc Grinders ONLY)
Part # QC-PCD1-B

GRIND:

Hard Thin Coatings, Concrete Sealers, Mortar Based Thinset, Light Concrete Leveling, Smooth/Level Concrete Imperfections

DOUBLE DYMA-DOTS

IDEAL FOR:

General removal of Epoxies, Residual Mastics, Thin-sets (yellow only), and other coverings. Leaves clean smooth surfaces with small amount of scratches and no gouging. General Purpose tool used for a wide range of prepping and removal applications. (Packs of 3)

Classification: Omni-Directional
Concrete Surface Profile: CSP 1-2



SOFT CONCRETE
(Yellow)
30 Grit Part # QC2B-SC-0030
70 Grit Part # QC2B-SC-0070
120 Grit Part # QC2B-SC-0120



MEDIUM CONCRETE
(Grey)
30 Grit Part # QC2B-MC-0030
70 Grit Part # QC2B-MC-0070
120 Grit Part # QC2B-MC-0120



HARD CONCRETE
(Red)
30 Grit Part # QC2B-HC-0030
70 Grit Part # QC2B-HC-0070
120 Grit Part # QC2B-HC-0120

DYMA-SEGS

IDEAL FOR:

General purpose aggressive grind. Designed for coatings and concrete removal. Leaves clean smooth surfaces with medium amounts of scratches. Available in Coarse Grit only. (Packs of 3)

Classification: Omni-Directional
Concrete Surface Profile: CSP 2



SOFT CONCRETE
18 Grit (Yellow)
Part # QC2S-SC-0018



MEDIUM CONCRETE
18 Grit (Grey)
Part # QC2S-MC-0018



HARD CONCRETE
18 Grit (Red)
Part # QC2S-HC-0018

ECONOMY GRINDING TOOL


IDEAL FOR:

Smoothing concrete, thin hard coating removal, and common surface prep tasks. (Packs of 3)

Classification: Omni-Directional




SOFT CONCRETE
(Yellow)
Part # M501SC



MEDIUM CONCRETE
(Grey)
Part # M501MC



LEFT-HAND
(Blue, For use on Single & Dual-Disc Grinders)
Part # M401PL



RIGHT-HAND
(Black, For Dual-Disc Grinders ONLY)
Part # M401PR

ECONOMY REMOVAL TOOL

IDEAL FOR:

Texturing concrete, thick hard coating removal, and industrial strength coating removal (Packs of 3)

Classification: Directional

MAGNA-TRAP SPECIALTY TOOLING

SINGLE DYMA-DOTS


IDEAL FOR:

Aggressively Grinding concrete. Removes epoxies, and other hard coatings. Leaves a clean surface with medium amount of scratches. General Purpose commonly used for prepping surfaces and removing coatings. (Packs of 3)

Classification: Omni-Directional
Concrete Surface Profile: CSP 2



SOFT CONCRETE
30 Grit (Yellow)
Part # QC1B-SC-0030



MEDIUM CONCRETE
30 Grit (Grey)
Part # QC1B-MC-0030



HARD CONCRETE
30 Grit (Red)
Part # QC1B-HC-0030

DYMA-CRUSH

IDEAL FOR:

Removing hard coatings and glue. Creates consistent lighter surface textures similar to a shot blast finish. (Packs of 3)

Classification: Omni-Directional
Concrete Surface Profile: CSP 3




DYMA-Crush
Part # QC2C-PCD

DYMA-ARROWS

IDEAL FOR:


Removing hard brittle glues and sealers from concrete, leaving a clean smooth surface with medium amount of scratches. (Packs of 3)

Classification: Directional
Concrete Surface Profile: CSP 2



SOFT CONCRETE
(Yellow, Left-Hand Arrow, For use on Single & Dual-Disc Grinders)
Part # QCAR-SC-0030-L

SOFT CONCRETE
(Green, Right-Hand Arrow, For use on Dual-Disc Grinders ONLY)
Part # QCAR-SC-0030-R



MEDIUM CONCRETE
(Grey, Left-Hand Arrow, For use on Single & Dual-Disc Grinders)
Part # QCAR-MC-0030


MEDIUM CONCRETE
(Black, Right-Hand Arrow, For use on Dual-Disc Grinders ONLY)
Part # QCAR-MC-0030-R

DYMA-PCD: EXTREME REMOVAL

IDEAL FOR:

Heavy fast removal of thick or hard coatings & waterproofing membrane. Leaves a rough surface texture and can potentially create heavy scratch marks on concrete. (Packs of 3)

Classification: Directional
Concrete Surface Profile: CSP 2-3



LEFT-HAND PCD
(Blue, For use on Single & Dual-Disc Grinders)
Part # QC-PCD1-L




RIGHT-HAND PCD
(Black, For use on Dual-Disc Grinders ONLY)
Part # QC-PCD1

MAGNA-SPIKES

IDEAL FOR:

Bush Hammer designed to prep surface for epoxy coatings, self leveling or polymer overlays. Can work for removal of thin coatings.

Classification: Omni-Directional
Concrete Surface Profile: CSP 3




ONLY FOR USE ON DUAL DISC GRINDERS
ONLY MODELS:
2EC-NG, 2GC-NG, & 2DH-HD
Part # QC-SPIKES

AGGREGATE CLASSIFICATION MAP













An important factor affecting the performance of diamond tooling is the type of aggregate inside the concrete or asphalt resurfaced worked. Aggregate is defined as the stone, gravel and sand used in paving materials like concrete and asphalt. Aggregate may be crushed or uncrushed. Crushed aggregate may be limestone, granite, sandstone, traprock, etc. Sand and gravel are typically found in natural deposits, like riverbeds, stream courses or lake basins.

While recognizing that aggregate size and type can change completely in a short distance on a given project, it is generally true that aggregates are similar in certain geographical areas. This map is not intended, nor should it be used to precisely define all aggregate in a given area. Instead, it is a general guide to the predominant aggregate in an area.



	SOFT CONCRETE	MEDIUM CONCRETE	HARD CONCRETE
HARDNESS	2000 - 4000 PSI Green concrete, coastal concrete, thinset mortar	4000 - 6000 PSI Residential and commercial concrete, sidewalks	6000 - 8000 PSI Industrial facilities, tight troweled, bridges, airport runways
AGGREGATE TYPE	Sandstone, Shell, Some Limestone, Some Marble, Green (New) Concrete	Traprock, Some Limestone, Dolomite, Some Granite, Some Marble	River Rock, Quartz, Flint Rock, Some Granite
MOHS SCALE	2-3	3-5	5-7

CLASSIC TOOLING

			
7" DIAMOND CUP WHEELS	7", 8 SEG PCD CUP WHEEL WITH BACKER	7" SCARIFIER ASSEMBLY	10" GENERAL PURPOSE DISC
40-50 Grit PART # 72029 Medium Bond PART # 72030 Hard Bond	Part# 72042	PART # 72040	PART # 19169 (Economy)
DESCRIPTION: 17 Segmented, dry cut grinding wheel. Grind Concrete and or remove coatings. Cup Wheels can be used with the Rigid Head or Flex Head Assembly.	DESCRIPTION: 8 Segmented, heavy fast removal of thick or hard coatings and waterproof membranes. For Rigid Head Assembly use only.	DESCRIPTION: 15 - Point Carbide Cutter Disc Assembly. Remove paint build-ups and coatings. Scarifier Assembly Discs can only be used with the Rigid Head Assembly on EDCO's TMC-7.	DESCRIPTION: 30-40, GRIT - 20 Segment Disc General purpose concrete. Hard Bond
			
10" GENERAL PURPOSE DISC	10" GENERAL PURPOSE DISC	10" GENERAL PURPOSE DISC	
PART # 19165 (Premium)	PART # 19161 (White)	PART # 19162 (Orange)	
DESCRIPTION: 30-40, GRIT - 20 Segment Disc General purpose concrete. Hard Bond	DESCRIPTION: 30-40, GRIT - 20 Segment Disc General purpose concrete. Medium Bond	DESCRIPTION: 30-40, GRIT - 20 Segment Disc General purpose concrete. Soft Bond	
			
DYMA-SERTS	PCDYMA-SERTS	STRIP-SERTS COMPLETE ASSEMBLY	PRO TUNGSTEN CARBIDE REPLACEMENT PACK
PART # 19110 - General Purpose 1x (30-40 Grit, Gold)	PART # 19155	PART # 12420 (Left Hand)	PART # 12407 (Pack of 6 Pro Tungsten II)
PART # 19130 - Abrasive 2x (30-40 Grit, Silver)		PART # 12424 (Right Hand)	
DESCRIPTION: For general purpose grinding of bare concrete and thinner hard coatings. Ideal for erasing concrete surface imperfections, light concrete leveling, and coatings removal. Leaves clean smooth surface with small amount of scratches and no gouging. HOLDING CASE Part# 19360	DESCRIPTION: Ideal for removal of hard and tacky surfaces including urethane epoxy, multi-part epoxy, waterproofing membrane, pool deck coating. Thick membrane, thick mastics, old and new epoxy coatings. HOLDING CASE Part# 19360	DESCRIPTION: Strip-Serts are used for stripping away coatings and cleaning floors without grinding into the concrete. It's replaceable, multi-sided tungsten carbide blocks can be rotated for maximum use. Removes Thicker/Soft coatings like mastics, tacky paint, resins, tar, fiberglass, ice and industrial buildups.	DESCRIPTION: Replaceable, 4-sided tungsten carbide edge that can be rotated for maximum use. For use on Magna-Trap® Strip-Serts Classic Floor Grinder Strip-Serts NOT for use on Magna-Blades or New Multi-Tooling Discs with Carbide Pockets.

VISIT EDCOinc.com for more classic tooling.

1-800-638-3326 • edcoinc.com • edcostore.com • edcoed.com